







READY FOR EFFICIENCY



Android 12 OS Simplify your workday

With the Android 12 OS, the PNC460 delivers the familiar experience and ease of use that the professionals want. More importantly, it provides an open and inclusive platform to run a wide variety of key apps, making everyday tasks easier and faster.



Hytera-developed Toolkit **Help you work better**

With versatile ready-to-use Hytera-developed tools such as high beam, noise meter, gradienter, altimeter, plumb, pedometer, and protractor, the PNC460 lets you work efficiently and effortlessly.





Exceptional Durability Withstand the tough conditions

The PNC460 is perfect for professionals working in the most demanding environments. It has tough exteriors and reinforced components to survive dust, water, snow, 1.5-meter sudden drops, extreme temperatures (–20°C to +60°C), and more.



GROSS WT. PAYLOAD TARE WT. CUBE

+



As a good assistant, the PNC460 helps you work more efficiently. The stunning 5-inch screen gives you plenty of space to use multiple apps at work. Additionally, this screen is sunlight readable and sensitive enough to react the touch of gloved hands and wet fingers.



Precise Positioning

Pinpoint your device and personnel

Thanks to the built-in dual-frequency GPS (L1+L5) chip, the PNC460 provides real-time, precise location for the dispatche with the accuracy improved to 2 meters. Know where your devices are. Keep your personnel safe.





Push-to-Talk **Stay connected anywhere, anytime**

With the Hytera HyTalk Pro app, the PNC460 can communicate with PDT, DMR, or TETRA radio over the 2G, 3G, LTE, or WLAN network. It delivers instant one-to-one or one-to-group communications anywhere in the world once you press down the large and tactile PTT key. This ensures flow of information at all time, even during the most critical circumstances.





Professional Acoustic System **Deliver loud and clear audio**

With the powerful speaker and sophisticated noise cancellation technologies, the PNC460 delivers crystal-clear audio in any noisy environment such as electrical maintenance field, port, and factory. This best-in-class audio promises a high-quality communication experience in any work environments.

Boosted Loudness

• 3-watt ultra linear dual-speaker

Maximized Clarity

- Al-based noise cancellation
- Echo reduction
- Wind noise cancellation
- Feedback howling reduction



External Antenna Make communications smoother and more stable

Unlike the radios with the built-in antenna, the PNC460 comes with the external antenna that has a 70% higher RX capability. So even in the area with weak signal strength such as mountain and underground garage, the PNC460 still conveys accurate information without missing any words.



Powerful Camera System Improve situational awareness

The PNC460 has unmatched photography capabilities, thanks to a 50 MP rear camera HDR technology, and image stabilization algorithm. It can capture clear pictures and stable live videos in the field, and feed them to the command center in real time over the LTE or WLAN network. This is invaluable for dispatcher to know what happened, significantly improving collaboration and outcomes.

Application Scenarios





Transportation







Customs Airport Logistics

Specifications

Frequency Range	GSM: 850/900/1800/1900
	WCDMA: B1/B2/B3/B4/B5/B8
	TDD-LTE: B34/B38/B39/B40/B41 (2496-2690 MHz)
	FDD-LTE: B1/B2/B3/B4/B5/B7/B8/B12/B13/B17/B20/B26/B28
Operating System	Android 12
Storage	4 GB RAM + 64 GB ROM
TF Card	128 GB (max.)
Weight	275 g
Screen Size	5.0 inches
Screen Resolution	1920 × 1080
SIM Slots	2 × Nano-SIM
Location	GPS (L1&L5)/A-GPS/BDS/GLONASS/Galileo
Sensor	Acceleration/gyroscope/geomagnetic/opto-sensor
WLAN	2.4 GHz&5 GHz, 802.11 a/b/g/n/ac
BT	BT 5.0
NFC	Available
Interfaces	USB Type-C port
	3.5 mm audio jack
Battery Capacity	4,500 mAh
Charging Interface	USB Type-C port
Speaker	3 W (max.)
Motor	Available
Cameras	Rear: 50 MP; Front: 8 MP
Video Resolution	1080p@60fps
Operating Temperature	-20°C to +60°C
Storage Temperature	−30°C to +70°C
Electro-Static Discharge (ESD)	IEC 61000-4-2
	±12 kV (air)
	±6 kV (contact)
IP Rating	IP68
Drop Resistance	1.5 m

Accessories





